

## DECLARATION OF PERFORMANCE, No 2024/01/02-DoP-HW-01

**1. Identification code of the product-type:**

Structural hardwood or combi plywood, coated or uncoated, 9-50 mm.

**2. Intended uses:**

For uncoated and surface unprotected plywood as a structural component according to EN 636-2.

For coated and/or surface protected plywood as a structural component according to EN 636-3.

**3. Manufacturer:**

Paged Morąg S.A.  
ul. Kwiatowa 1  
12-200 Pisz

Paged Morąg S.A.  
ul. Mazurska 1  
14-300 Morąg

**5. System of AVCP:**

AVCP system 2+

**6a. Harmonized standard:**

EN 13986:2004+A1:2015

Paged Morąg  
ul. Kwiatowa 1  
12-200 Pisz, Poland  
0763-CPR-6079  
0763-CPR-6071  
0763-CPR-6073

Paged Morąg  
ul. Mazurska 1  
14-300 Morąg, Poland  
0763-CPR-6086  
0763-CPR-6006  
0763-CPR-6080

**Notified body**

MPA Eberswalde - Materialprüfanstalt Brandenburg GmbH (Approved body No 0763)  
Alfred-Möller-Straße 1  
16225 Eberswalde  
Germany

## 7. Declared performance:

| Hardwood plywood                   |                                    |                                                                                  |                       |                   |        |
|------------------------------------|------------------------------------|----------------------------------------------------------------------------------|-----------------------|-------------------|--------|
| Essential characteristics          | End use condition                  | min. thickness (mm)                                                              | Performance           |                   |        |
| Reaction to fire                   |                                    |                                                                                  | Class (ex. floorings) | Class (floorings) |        |
|                                    |                                    | without an air gap behind the wood-based panel                                   | 9                     | D-s2, d0          | Dfl-s1 |
|                                    |                                    | with a closed or an open air gap not more than 22 mm behind the wood-based panel | 9                     | D-s2, d2          | -      |
|                                    |                                    | with a closed air gap behind the wood-based panel                                | 15                    | D-s2, d1          | Dfl-s1 |
|                                    |                                    | with an open air gap behind the wood-based panel                                 | 18                    | D-s2, d0          | Dfl-s1 |
|                                    | any                                | 3                                                                                | E                     | Efl               |        |
| Essential characteristics          |                                    | Performance                                                                      |                       |                   |        |
| Water vapour permeability          |                                    | Wet cup μ - 90<br>Dry cup μ - 220                                                |                       |                   |        |
| Release of formaldehyde            |                                    | Class E1                                                                         |                       |                   |        |
| Content of pentachlorophenol (PCP) |                                    | None                                                                             |                       |                   |        |
| Airborne sound insulation          |                                    | NPD                                                                              |                       |                   |        |
| Sound absorption α                 | Range                              |                                                                                  | α                     |                   |        |
|                                    | 250-500 Hz                         |                                                                                  | 0,10                  |                   |        |
|                                    | 1000-2000 Hz                       |                                                                                  | 0,30                  |                   |        |
| Thermal conductivity λ (W/(mK))    |                                    | 0,17                                                                             |                       |                   |        |
| Bonding quality                    |                                    | Class 3                                                                          |                       |                   |        |
| Biological durability              | Uncoated or coated and unprotected |                                                                                  | Use class 2           |                   |        |
|                                    | Coated with protected edges        |                                                                                  | Use class 3           |                   |        |
| Embedment strength                 |                                    | NPD                                                                              |                       |                   |        |
| Air permeability                   |                                    | NPD                                                                              |                       |                   |        |
| Racking resistance                 |                                    | NPD                                                                              |                       |                   |        |
| Density range (kg/m³)              |                                    | 640-760                                                                          |                       |                   |        |

Harmonized standard EN 13986+A1:2015

Harmonized standard EN 13986+A1:2015

| Nominal thickness                                      | 9           | 12   | 15   | 18 | 21   | 24 | 27   | 30 | 35 | 40 | 45 | 50 |
|--------------------------------------------------------|-------------|------|------|----|------|----|------|----|----|----|----|----|
| Essential characteristics                              | Performance |      |      |    |      |    |      |    |    |    |    |    |
| Bending strength class acc. to EN 636                  |             |      |      |    |      |    |      |    |    |    |    |    |
| II                                                     | F40         |      |      |    | F35  |    | F40  |    |    |    |    |    |
| ⊥                                                      | F35         |      |      |    | F30  |    | F30  |    |    |    |    |    |
| Characteristic bending strength acc. to EN 636 (N/mm²) |             |      |      |    |      |    |      |    |    |    |    |    |
| f <sub>m</sub> II                                      | 60          |      |      |    | 52   |    | 60   |    |    |    |    |    |
| f <sub>m</sub> ⊥                                       | 52          |      |      |    | 45   |    | 45   |    |    |    |    |    |
| Characteristic compression strength                    | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| Characteristic tension strength                        | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| E class in bending MOE acc. to EN 636                  |             |      |      |    |      |    |      |    |    |    |    |    |
| II                                                     | E80         | E80  | E80  |    | E70  |    | E70  |    |    |    |    |    |
| ⊥                                                      | E50         | E60  | E70  |    | E60  |    | E50  |    |    |    |    |    |
| Mean MOE in bending acc. to EN 636 (N/mm²)             |             |      |      |    |      |    |      |    |    |    |    |    |
| E <sub>m</sub> II                                      | 7200        | 7200 | 7200 |    | 6300 |    | 6300 |    |    |    |    |    |
| E <sub>m</sub> ⊥                                       | 4500        | 5400 | 6300 |    | 5400 |    | 4500 |    |    |    |    |    |
| Mean MOE in compression and tension                    | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| Char. panel shear                                      | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| Char. planar shear                                     | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| Mean MOR in panel shear                                | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| Mean MOR in planar shear                               | NPD         |      |      |    |      |    |      |    |    |    |    |    |

Harmonized standard EN 13986+A1:2015

Harmonized standard EN 13986+A1:2015

| Combi plywood                      |                                    |                                                                                  |                       |                   |        |
|------------------------------------|------------------------------------|----------------------------------------------------------------------------------|-----------------------|-------------------|--------|
| Essential characteristics          | End use condition                  | min. thickness (mm)                                                              | Performance           |                   |        |
| Reaction to fire                   |                                    |                                                                                  | Class (ex. floorings) | Class (floorings) |        |
|                                    |                                    | without an air gap behind the wood-based panel                                   | 9                     | D-s2, d0          | Dfl-s1 |
|                                    |                                    | with a closed or an open air gap not more than 22 mm behind the wood-based panel | 9                     | D-s2, d2          | -      |
|                                    |                                    | with a closed air gap behind the wood-based panel                                | 15                    | D-s2, d1          | Dfl-s1 |
|                                    |                                    | with an open air gap behind the wood-based panel                                 | 18                    | D-s2, d0          | Dfl-s1 |
|                                    | any                                | 3                                                                                | E                     | Efl               |        |
| Essential characteristics          |                                    | Performance                                                                      |                       |                   |        |
| Water vapour permeability          |                                    | Wet cup μ - 90<br>Dry cup μ - 220                                                |                       |                   |        |
| Release of formaldehyde            |                                    | Class ½ E1                                                                       |                       |                   |        |
| Content of pentachlorophenol (PCP) |                                    | None                                                                             |                       |                   |        |
| Airborne sound insulation          |                                    | NPD                                                                              |                       |                   |        |
| Sound absorption α                 | Range                              |                                                                                  | α                     |                   |        |
|                                    | 250-500 Hz                         |                                                                                  | 0,10                  |                   |        |
|                                    | 1000-2000 Hz                       |                                                                                  | 0,30                  |                   |        |
| Thermal conductivity λ (W/(mK))    |                                    | 0,17                                                                             |                       |                   |        |
| Bonding quality                    |                                    | Class 3                                                                          |                       |                   |        |
| Biological durability              | Uncoated or coated and unprotected |                                                                                  | Use class 2           |                   |        |
|                                    | Coated with protected edges        |                                                                                  | Use class 3           |                   |        |
| Embedment strength                 |                                    | NPD                                                                              |                       |                   |        |
| Air permeability                   |                                    | NPD                                                                              |                       |                   |        |
| Racking resistance                 |                                    | NPD                                                                              |                       |                   |        |
| Density range (kg/m³)              |                                    | 580-700                                                                          |                       |                   |        |

Harmonized standard EN 13986+A1:2015

Harmonized standard EN 13986+A1:2015

| Nominal thickness                                      | 9           | 12   | 15   | 18 | 21   | 24 | 27   | 30 | 35 | 40 | 45 | 50 |
|--------------------------------------------------------|-------------|------|------|----|------|----|------|----|----|----|----|----|
| Essential characteristics                              | Performance |      |      |    |      |    |      |    |    |    |    |    |
| Bending strength class acc. to EN 636                  |             |      |      |    |      |    |      |    |    |    |    |    |
| II                                                     | F40         |      |      |    | F35  |    | F40  |    |    |    |    |    |
| ⊥                                                      | F35         |      |      |    | F30  |    | F30  |    |    |    |    |    |
| Characteristic bending strength acc. to EN 636 (N/mm²) |             |      |      |    |      |    |      |    |    |    |    |    |
| f <sub>m</sub> II                                      | 60          |      |      |    | 52   |    | 60   |    |    |    |    |    |
| f <sub>m</sub> ⊥                                       | 52          |      |      |    | 45   |    | 45   |    |    |    |    |    |
| Characteristic compression strength                    | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| Characteristic tension strength                        | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| E class in bending MOE acc. EN 636                     |             |      |      |    |      |    |      |    |    |    |    |    |
| II                                                     | E80         | E90  | E80  |    | E70  |    | E70  |    |    |    |    |    |
| ⊥                                                      | E50         | E70  | E70  |    | E60  |    | E60  |    |    |    |    |    |
| Mean MOE in bending acc. to EN 636 (N/mm²)             |             |      |      |    |      |    |      |    |    |    |    |    |
| E <sub>m</sub> II                                      | 7200        | 8100 | 7200 |    | 6300 |    | 6300 |    |    |    |    |    |
| E <sub>m</sub> ⊥                                       | 4500        | 6300 | 6300 |    | 5400 |    | 5400 |    |    |    |    |    |
| Mean MOE in compression and tension                    | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| Char. panel shear                                      | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| Char. planar shear                                     | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| Mean MOR in panel shear                                | NPD         |      |      |    |      |    |      |    |    |    |    |    |
| Mean MOR in planar shear                               | NPD         |      |      |    |      |    |      |    |    |    |    |    |

Harmonized standard EN 13986+A1:2015

Harmonized standard EN 13986+A1:2015

Performance of this product, as identified above, is in conformity with the set declared performances and characteristics. This declaration of performance is issued in accordance with Regulation EU No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Pisz, POLAND, 2nd January 2024

  
*Jarosław Wasiuk*  
Dyrektor Sprzedaży Eksportowej  
Export Sales Director