

*efficiency  
poplar*

100% EUROPEAN  
POPLAR LIGHTWEIGHT  
PLYWOOD

• INCREDIBLY LIGHTWEIGHT. •

Composition  
100% planted  
European poplar

*Versatility  
that challenges  
creativity*



**Smoothness and stability**

Ideal for painting or covering.



**Easily machinable**

Very easy to cut and sand.



**Sustainability**

Certified fast-growing European plantations.



**PRM**

Available with primed finish ready for a final coat of paint.

**garnica**

Challenge the ordinary

CE

Certifications on demand:



The mark of responsible forestry  
This logo only refers to FSC-MIX products



CE 2+

CARB Phase 2 / TSCA Title VI

**efficiency  
poplar**

## 100% EUROPEAN POPLAR LIGHTWEIGHT PLYWOOD

Lightweight panel made entirely of European poplar sourced from sustainable plantations. Its light colour and the smoothness of the veneers make it ideal for painting or covering.

Available with **PRM** primed finish with 80 microns of water-based acrylic paint, designed to reduce time and cost for the end user who finishes the board with a final coat of paint.

Maximum sustainability due to its poplar core sourced from fast-growing plantations. This wood provides lightness, stability, surface quality and machinability.

**Applications:** Extremely versatile range that translates into a multitude of applications, such as interior construction, furniture manufacturing for caravans or vans and public and private establishments.

**Glue Type:** Class I (interior) and Class III (exterior) according to EN 636

**Emissions:** Class E1 according to EN 13986

## Furniture for camper vans



## Interior construction



| Formats         |              | Quality faces: B/BB |    |    |    |    |    |    |    |    |    |    |    |    |
|-----------------|--------------|---------------------|----|----|----|----|----|----|----|----|----|----|----|----|
|                 |              | Thickness (mm)      |    |    |    |    |    |    |    |    |    |    |    |    |
| Dimensions (mm) |              | 6                   | 7  | 8  | 9  | 10 | 12 | 15 | 18 | 20 | 22 | 25 | 30 | 40 |
| 2440 x 1220     | No. of plies | 3                   | 5  | 5  | 5  | 5  | 7  | 7  | 9  | 9  | 9  | 11 | 13 | 15 |
| 2500 x 1220     | Packaging    | 100                 | 85 | 75 | 70 | 60 | 50 | 40 | 33 | 30 | 27 | 24 | 20 | 15 |
| 2520 x 1850     | No. of plies | -                   | -  | 5  | -  | 5  | 7  | 7  | 9  | 9  | 9  | 11 | 13 | 15 |
|                 | Packaging    | -                   | -  | 75 | -  | 60 | 50 | 40 | 33 | 30 | 27 | 24 | 20 | 15 |
| 3100 x 1530     | No. of plies | -                   | -  | 5  | 5  | 5  | 7  | 7  | 9  | -  | 9  | 11 | 13 | 15 |
| 3100 x 1850     | Packaging    | -                   | -  | 62 | 55 | 50 | 41 | 33 | 27 | -  | 22 | 20 | 16 | 12 |



| Formats         |              | Quality faces: BB/BB |     |     |    |    |    |    |    |    |    |    |    |
|-----------------|--------------|----------------------|-----|-----|----|----|----|----|----|----|----|----|----|
|                 |              | Thickness (mm)       |     |     |    |    |    |    |    |    |    |    |    |
| Dimensions (mm) |              | 4                    | 5   | 6   | 8  | 9  | 10 | 12 | 15 | 18 | 22 | 30 | 40 |
| 2440 x 1220     | No. of plies | 3                    | 3   | 3   | 5  | 5  | 5  | 7  | 7  | 9  | 9  | 13 | 15 |
| 2500 x 1220     | Packaging    | 150                  | 120 | 100 | 75 | 70 | 60 | 50 | 40 | 33 | 27 | 20 | 15 |
| 2520 x 1850     | No. of plies | -                    | 3   | -   | 5  | -  | -  | -  | -  | -  | -  | -  | -  |
|                 | Packaging    | -                    | 120 | -   | 75 | -  | -  | -  | -  | -  | -  | -  | -  |
| 3100 x 1530     | No. of plies | -                    | 3   | -   | -  | -  | 5  | -  | 7  | 9  | -  | -  | -  |
|                 | Packaging    | -                    | 50  | -   | -  | -  | 50 | -  | 33 | 27 | -  | -  | -  |



### Technical features

|  | Values      | Standard |
|--|-------------|----------|
| Density (Kg/m <sup>3</sup> )               | 420-480     | EN 323   |
| Modulus of elasticity (N/mm <sup>2</sup> ) | 3.500-4.800 | EN 310   |
| Face Screw Holding (kgf)                   | 135         | EN 320   |
| Moisture content (%)                       | 6-14        | EN 322   |

@ info@garnica.one

@garnicaplywood

@garnicaplywood

Garnica Plywood

Garnica

@garnicaplywood

www.garnica.one

**garnica**