

*efficiency  
poplar*

## 100% EUROPEAN POPLAR LIGHTWEIGHT PLYWOOD

• INCREDIBLY LIGHTWEIGHT. •

Composition  
100% planted  
European poplar

*Versatility  
that challenges  
creativity*



### **Smoothness and stability**

Ideal for painting or covering.



### **Easily machinable**

Very easy to cut and sand.



### **Sustainability**

Certified fast-growing European plantations.



### **PRM**

Available with primed finish ready for a final coat of paint.

**garnica**

Challenge the ordinary

CE

Certifications on demand:



The mark of  
responsible forestry  
This logo only refers  
to FSC® products



CE 2+

CARB Phase 2 / TSCA Title VI

## 100% EUROPEAN POPLAR LIGHTWEIGHT PLYWOOD

Lightweight panel made entirely of European poplar sourced from sustainable plantations. Its light colour and the smoothness of the veneers make it ideal for painting or covering.

Available with **PRM** primed finish with 80 microns of water-based acrylic paint, designed to reduce time and cost for the end user who finishes the board with a final coat of paint.

Maximum sustainability due to its poplar core sourced from fast-growing plantations. This wood provides lightness, stability, surface quality and machinability.

**Applications:** Extremely versatile range that translates into a multitude of applications, such as interior construction, furniture manufacturing for caravans or vans and public and private establishments.

**Glue Type:** Class I (interior) and Class III (exterior) according to EN 636

**Emissions:** Class E1 according to EN 13986

### Formats Quality faces: B/BB

|                            |              | Thickness (mm) |    |    |    |    |    |    |    |    |    |    |    |    |  |
|----------------------------|--------------|----------------|----|----|----|----|----|----|----|----|----|----|----|----|--|
| Dimensions (mm)            |              | 6              | 7  | 8  | 9  | 10 | 12 | 15 | 18 | 20 | 22 | 25 | 30 | 40 |  |
| 2440 x 1220<br>2500 x 1220 | No. of plies | 3              | 5  | 5  | 5  | 5  | 7  | 7  | 9  | 9  | 9  | 11 | 13 | 15 |  |
|                            | Packaging    | 100            | 85 | 75 | 70 | 60 | 50 | 40 | 33 | 30 | 27 | 24 | 20 | 15 |  |
| 2520 x 1850                | No. of plies | -              | -  | 5  | -  | 5  | 7  | 7  | 9  | 9  | 9  | 11 | 13 | 15 |  |
|                            | Packaging    | -              | -  | 75 | -  | 60 | 50 | 40 | 33 | 30 | 27 | 24 | 20 | 15 |  |
| 3100 x 1530<br>3100 x 1850 | No. of plies | -              | -  | 5  | 5  | 5  | 7  | 7  | 9  | -  | 9  | 11 | 13 | 15 |  |
|                            | Packaging    | -              | -  | 62 | 55 | 50 | 41 | 33 | 27 | -  | 22 | 20 | 16 | 12 |  |

### Formats Quality faces: BB/BB

|                 |              | Thickness (mm) |     |     |    |    |    |    |    |    |    |    |    |
|-----------------|--------------|----------------|-----|-----|----|----|----|----|----|----|----|----|----|
| Dimensions (mm) |              | 4              | 5   | 6   | 8  | 9  | 10 | 12 | 15 | 18 | 22 | 30 | 40 |
| 2440 x 1220     | No. of plies | 3              | 3   | 3   | 5  | 5  | 5  | 7  | 7  | 9  | 9  | 13 | 15 |
|                 | Packaging    | 150            | 120 | 100 | 75 | 70 | 60 | 50 | 40 | 33 | 27 | 20 | 15 |
| 2520 x 1850     | No. of plies | -              | 3   | -   | 5  | -  | -  | -  | -  | -  | -  | -  | -  |
|                 | Packaging    | -              | 120 | -   | 75 | -  | -  | -  | -  | -  | -  | -  | -  |
| 3100 x 1530     | No. of plies | -              | 3   | -   | -  | -  | 5  | -  | 7  | 9  | -  | -  | -  |
|                 | Packaging    | -              | 50  | -   | -  | -  | 50 | -  | 33 | 27 | -  | -  | -  |

**PRM**

### Technical features

|                                            | Values      | Standard |
|--------------------------------------------|-------------|----------|
| Density (Kg/m <sup>3</sup> )               | 420-480     | EN 323   |
| Modulus of elasticity (N/mm <sup>2</sup> ) | 3.500-4.800 | EN 310   |
| Face Screw Holding (kgf)                   | 135         | EN 320   |
| Moisture content (%)                       | 6-14        | EN 322   |

## Furniture for camper vans



## Interior construction



@ info@garnica.one

@garnicaplywood

@garnicaplywood

Garnica Plywood

Garnica

@garnicaplywood

www.garnica.one

**garnica**