

- 1 Unique identification code of the product-type: **PRINT HPL MEG thickness $\geq 6,0$ mm**
2. Intended use: **HPL laminate used as external wall and ceiling finishes**
3. Manufacturer: **ABET LAMINATI spa - Viale Industria, 21 - 12042 BRA (CN) - Italy
Tel. +39 0172 419 111 - Fax: +39 0172 431571 - Email: abet@abet-laminati.it**
4. Systems of AVCP: **system 3**
5. Harmonised standard: **EN 438-7: 2005**
6. Notify Body: **CSI SpA - n° 0497**
7. Performance

Essential characteristics	Performance
Reaction to fire	C-s2,d0 thickness ≥ 6 mm mounted on aluminium tubular rods B-s1,d0 thickness ≥ 12 mm fixed on any kind of frame
Resistance to fire	NPD
Water vapour permeability	NPD
Resistance to fixings	2000 N (6 mm) 3000 N (8 mm) 4000 N (≥ 10 mm)
Direct airborne sound insulation	NPD
Flexural tensile strength	PASS
Thermal resistance/conductivity	NPD
Thermal shock resistance	PASS
Release of formaldehyde	Class E1
Durability Resistance to wet conditions Density	PASS ≥ 1350 kg/m ³

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Bra, 09/09/2019



Luciano Menegaldo
Technology Department